ⓘ Coming October 20th, discover our sleek new design and powerful features. Learn More

UL Product iQ®

Low-expansion Foam Liquid Concentrate HD AFFF 3FZ-C6

File Number: EX15756

COMPANY

HD FIRE PROTECT LIMITED
D-6/2, Road No. 34
Wagle Industrial Estate
Thane, Maharashtra 400604 India

LOW-EXPANSION FOAM LIQUID CONCENTRATE INFO

HD AFFF 3FZ-C6
Aqueous Film Forming Foam (AFFF)

FOAM CONCENTRATES FOR USE WITH THE FOLLOWING EQUIPMENT

Minimum Storage and Use Temperature
0 F (-17.8 C)

GENERAL

Hydrocarbon Fuels, percent
3

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Manufacturer and Model	Use Concentration, percent	Size, in.	Orifice Diameter/Setting	Inlet Pressure, psig	Length and Diameter of hose	Discharge Device Manufacturer and Model
Angus Fire Ltd., Model UNI225	3	2-1/2	set at 3	100	50 ft of 1-1/2	Angus Fire Ltd, Model F225U nozzle

NOZZLES

Manufacturer and Model	Size, in.	Inlet Pressure, psig	Fuel
Angus Fire (UK), Model F225U	2-1/2	64	--

Report Date: 2010-05-26
Revision Date: 2025-06-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."